#### MATERIAL SAFETY DATA SHEET

COMPLIES WITH OSHA'S HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200)

**SECTION I · PRODUCT IDENTIFICATION** 

Product Name: SURE FOOT Slip Resistant Coating - Gray

Product Number: 911 Product Type: AEROSOL

Supplier's Name: Terand Industries, Inc.

Supplier's Address: P.O. Box 667770, Pompano Beach, FL 33066 D.O.T. Hazard Class: CONSUMER COMMODITY · ORM-D

Formula: Proprietary Date Prepared: 12/28/07

**Emergency Phone:** (800) 535-5053 Information Phone: (954) 974-5440

1- Sliaht 0-Minimal 2- Moderate

3- Serious 4- Extreme

HEALTH: 2\* FIRE: 4 REACTIVITY: 0

HMIS Rating (Based on Aerosol Conc.):

Personal Protection: |

SECTION II - INGREDIENTS

|                                 | OLOTION II - INCINEDIENTO |       |          |      |            |                             |                             |
|---------------------------------|---------------------------|-------|----------|------|------------|-----------------------------|-----------------------------|
| CHEMICAL NAME                   | CAS#                      | %WT   | 313/Chem | Skin | Carcinogen | PEL                         | TWA/TLV                     |
| Acetone                         | 67-64-1                   | 10-20 | NO       | NO   | NO         | 750 ppm                     | 750 ppm                     |
| Epoxy Resin                     | Proprietary               | 10-20 | NO       | NO   | NO         | N/E                         | N/E                         |
| Propane                         | 74-98-6                   | 10-20 | NO       | NO   | NO         | 1000 ppm                    | 1000 ppm                    |
| Toluene                         | 108-88-3                  | 05-15 | YES      | YES  | NO         | 100 ppm                     | 50 ppm                      |
| Xylene                          | 1330-20-7                 | 05-15 | YES      | NO   | NO         | 100 ppm                     | 100 ppm                     |
| Butane                          | 106-97-8                  | 05-15 | NO       | NO   | NO         | 800 ppm                     | 800ppm                      |
| Ethyl Benzene                   | 100-41-4                  | 05-15 | YES      | NO   | IARC (2b)  | 100 ppm                     | 100 ppm                     |
| Titanium Dioxide (Dust Hazard)  | 13463-67-7                | 05-15 | NO       | NO   | NO         | 15 mg/m <sup>3</sup> (Dust) | 10 mg/m <sup>3</sup> (Dust) |
| Clay (Dust Hazard)              | 1332-58-7                 | 05-15 | NO       | NO   | NO         | 10 mg/m <sup>3</sup> (Dust) | 10 mg/m <sup>3</sup> (Dust) |
| Calcium Carbonate (Dust Hazard) | 1317-65-3                 | 05-15 | NO       | NO   | NO         | 15 mg/m <sup>3</sup> (Dust) | 10 mg/m <sup>3</sup> (Dust) |
| Iron Oxide (Dust Hazard)        | 1309-37-1                 | 05-15 | NO       | NO   | NO         | 10 mg/m <sup>3</sup> (Dust) | 10 mg/m <sup>3</sup> (Dust) |
| Amorphous Silica (Dust Hazard)  | 7631-86-9                 | 01-10 | NO       | NO   | NO         | 6 mg/m <sup>3</sup> (Dust)  | 6 mg/m <sup>3</sup> (Dust)  |
| D&C Orange No. 17               | 3468-63-1                 | 01-10 | NO       | NO   | NO         | 10 mg/m <sup>3</sup> (Dust) | 10 mg/m <sup>3</sup> (Dust) |

## **SECTION III · PHYSICAL DATA**

Data Below Based On Aerosol Concentrate Only:

Boiling Range: -13°F to 279° F

pH: N/A

Solubility In Water: Insoluble

Appearance/Odor: Colored Liquid, Solvent Odor Data Below Based On Total Contents: Vapor Pressure of can (psig @70°F): 65

Total VOC %: ~ 45%

Vapor Density(Air=1): >1

Specific Gravity (H<sub>2</sub>O=1)@75°F: 1.02

# SECTION IV · FIRE AND EXPLOSION DATA

Flash Point (of Concentrate & Propellant): -134°F

Flammability (as per USA Flame Projection Test): Extremely Flammable Spray

Extinguishing Media: Foam, CO<sub>2.</sub> Dry Media, Water fog

Special Fire Fighting Procedures: Hazardous decomposition products may form from incomplete combustion. Wear full protection gear with self-contained positive pressure breathing apparatus. Cool fire exposed containers to prevent rupturing.

Unusual Fire and Explosion Hazards: Extremely flammable liquid and vapors. Containers can build pressure from heat and rupture explosively. Volatile vapors can burn in the open or explode if confined. Vapor is heavy and can travel long distances to source of ignition.

# **SECTION V · REACTIVITY DATA**

Stability: Material Stable.

Hazardous Polymerization: Will not Occur.

Incompatibility: Avoid contact with strong oxidizing agents.

Hazardous Decomposition Products: Carbon Dioxide, Carbon Monoxide and potentially other toxic gases if incomplete combustion occurs.

#### SECTION VI · STORAGE AND HANDLING

KEEP OUT OF REACH OF CHILDREN.

For Industrial and Institutional use only

NFPA Code 30B Rating: Level 3 Aerosol.

Store in a cool, dry area away from heat or open flame. Do not store at temperatures above 120° F.

#### SECTION VII · HEALTH AND FIRST AID

## PRIMARY ROUTES OF ENTRY & EFFECTS OF OVER EXPOSURE:

Eyes: Can cause conjunctivitis, severe irritation, redness, tearing and blurred vision. Prolonged contact may cause damage to the cornea.

Skin: Frequent or prolonged contact will cause irritation, defatting of the skin, and dermatitis. May cause allergic skin reaction.

Inhalation: Inhalation of mist can cause irritation of nasal and respiratory passages. Abusive or excessive inhalation can cause irritation to the upper respiratory tract, dizziness, nausea and other central nervous system effects. Repeated and prolonged exposure to solvent vapors may cause permanent brain and nervous system damage. May also cause liver and kidney damage.

Ingestion: Can cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration of material into the lungs can cause chemical pneumonitis.

FIRST AID PROCEDURES:

Eyes: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention

Skin: Wash with soap and water. If irritation persists seek medical attention.

Inhalation: Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration or administer oxygen.

Ingestion: Do not induce vomiting. Seek medical attention immediately.

## **SECTION VIII · SPECIAL PROTECTION DATA**

Respiratory Protection: If ventilation is not adequate to reduce vapors below TLV levels, use a NIOSH approved air purifying respirator with organic vapor cartiridges. Ventilation: Provide local exhaust to keep concentration of Section II ingredients below acceptable limits.

Protective Gloves: Use chemical resistant gloves if hand contact will be made.

Eye Protection: Wear safety glasses or chemical proof goggles.

## SECTION IX - SPILL OR LEAK PROTECTION

STEPS TO BE TAKEN IN CASE OF SPILL OR LEAK: Allow propellant to evaporate. Maintain local exhaust and adequate ventilation. No smoking. Keep sparks, heat sources and open flame far away from spill or leak. Cover with absorbent material and sweep up. Wash area to prevent slipping. Dispose of soaked absorbent material in accordance with Federal. State and local laws.

WASTE DISPOSAL METHOD: Aerosol cans, when emptied and depressurized through normal use, pose no disposal hazard and should be recycled. Consult Federal, State and local authorities for approved procedures.

N/A= NOT APPLICABLE · N/E=NOT ESTABLISHED · N/D=NOT DETERMINED · <=LESS THAN · >=MORE THAN

NOTICE: The information contained on this Material Safety Data Sheet is considered accurate as of the date of publication. It is not necessarily all inclusive nor fully adequate in every circumstances. The suggestions should not be confused with, nor followed in violation of applicable laws, regulations, rules or insurance requirements. No warranty, express or implied, of merchantability, fitness, accuracy of data, or the results to be obtained from the use thereof is made. The vendor assumes no responsibility for injury or damages resulting from the inappropriate use of this product.